

# ASPHALT EMULSION

AQUEOUS-BASE WATERPROOFING PRIMER  
FOR ASPHALT MEMBRANES

**MEGAFLEX®**  
THE WATERPROOF BARRIER



**Easily  
cold-applied.**



**Does not shift  
when exposed  
to direct flame.**



**Nonflammable  
product.**

**Primer/  
Waterproof**

#### Yield

Varying, depending on  
surface absorption.  
(About 0.5 kg/m<sup>2</sup>)

#### How Supplied

4-Kg. plastic cans EB04  
18-Kg. plastic cans EB18  
18-kg. boxes (EC10)  
10-kg. boxes (EC10)  
200-kg. kegs (ET200)



## Features

Megaflex Asphalt Emulsion is a thick plastic asphalt-based waterproofing coat. Physico-chemically, it is a thixotropic mineral colloid, which, given its aqueous base, is cold-applied. Suitable for any kinds of roofings. It is also ideal for vertical surfaces, where it forms a perfectly elastic and waterproof film.

## Where

Complete or partial waterproofing: flat, curved or pitched roofs. Underlying waterproofing primer for asphalt membranes.

## Application

The application surface should be dry and clean. The asphalt emulsion can be applied by using a mop, a putty knife, a chip brush, a paint roller, or a blowtorch, depending on the original compound dilution level. Apply a first coating by diluting in 40% water, and a second coating by diluting the product in 10% water. Total or partial waterproofing requires a third undiluted coating and further protection with aluminized asphalt painting or Megaflex waterproof coating.

## Caution

Do not apply under rain forecast or unstable weather conditions. Dry and touch-dry times will vary depending on climate and weather conditions, such as room humidity, wind, and surface temperature. Dilute with water. Do not use kerosene or any other solvents.

## Advantages

Easily cold-applied.  
Does not shift when exposed to direct flame.  
Nonflammable product.  
Primer/Waterproof.

MK.106.R14.REV2

B1852LGX, 1760 Luis M. Drago St., Burzaco, Almirante Brown Industrial District, Buenos Aires (Argentina) / Tel. / Fax: (54-11) 4002-5000  
/E-mail: info@megaflex.com.ar / www.megaflex.com.ar / Technical Department: tecnico@megaflex.com.ar

**0-800-33-33-649 (MGX)**

Images are only illustrative

# ASPHALT PAINT

MULTI-PURPOSE SOLVENT-BASED ANTI-CORROSION  
WATERPROOFING PRIMER



Ultra fast dry  
solvent-based  
waterproof.

Substrate  
primer for  
waterproofing  
asphalt  
membranes.  
Waterproof.

Anti-corrosive  
agent.

Easily  
cold-applied.

#### How Supplied

- 1-L tin can (PA1)
- 4-L tin can (PA4)
- 18-L handled tin can (PA18)
- 200-L drum (PA200)



### Features

Solvent-based, ultra-fast drying, multi-purpose primer. Megaflex Asphalt Primer is a solution which combines oxidized asphalt bases and volatile solvents from petroleum distillation. The quick evaporation of the solvents results in a highly adherent and completely waterproof, flexible film.

Megaflex Asphalt Primer also works as an anti-corrosion coating. Because of its ultra-fast drying capability, it is ideal for works where drying time is crucial.

### Where

Waterproofing underlying primer for asphalt membranes. For waterproofing surfaces such as wood, fiber cement, cement, metal surfaces, etc. It can also be used as an anti-corrosion protection for metal roofs, plumbing, roofing, etc.

### Application

The application surface should be dry and clean. Use a wide brush, a paint roller, or a mop  
Flammable paint. Apply in cold.

### Yield

Primer: Suggested yield based on two coatings is about 0.5 L/m<sup>2</sup>.

### Caution

Flammable, ultra-fast dry product, containing highly volatile solvents. Keep away from heat sources or flames. Do not apply indoors. Make sure in all cases to provide an appropriate ventilation



MK.I06.R6.REV2

B1852LGX, 1760 Luis M. Drago St., Burzaco, Almirante Brown Industrial District, Buenos Aires (Argentina) / Tel. / Fax: (54-11) 4002-5000  
/E-mail: info@megaflex.com.ar / www.megaflex.com.ar / Technical Department: tecnico@megaflex.com.ar

**0-800-33-33-649 (MGX)**

Images are only illustrative