

GEOTRANS PAINT

WATERPROOF WALKABLE COATING FOR
GEOTRANS MEMBRANES

MEGAFLEX[®]
THE WATERPROOF BARRIER



- Protects GEOTRANS membrane and makes it walkable.

- Higher durability and resistance because of its elasticity.

- Excellent adhesion to different kinds of surfaces.

- Excellent aesthetic finish.

- Matt anti-reflex hues improve solar radiation resistance.

- Compatible with asphalt-based products.

- Easy application.

- Aqueous-base paint. Supports diluting with water.

How Supplied

4-Kg Plastic Can
(RIB4/RIV4/RIR4)
20-Kg Plastic Can
(RIB2/RIV2/RIR2)



Features

GEOTRANS paint is an acrylic waterproof coating specially made to be used over GEOTRANS membrane. Together, they make up a walkable waterproofing system with a strong mechanical resistance. GEOTRANS Paint protects the geotextile coating, providing better abrasion resistance and improving the waterproofing capacity. GEOTRANS paint turns into an elastic highly resistant waterproof film, which can efficiently cope with any foot traffic stress. GEOTRANS paint is highly resistant to sun radiation (matt anti-reflex hues) and is available in English green, fired brick red, and chalk white colors.

Where

Over Geotrans membrane.
Over in situ asphalt waterproofing.

Application

Apply on a perfectly clean and dry surface, using a roller or brush. First, paint the sheet lap joints, over the GEOTRANS membrane. Then, apply a smooth coating of paint on the whole surface, including the lap joints. Apply a second coating following the same procedure. It is recommended to use the product dissolved in water during the first coating, and use the undiluted product during the following ones. Always let dry before applying a new coating.

Yield

Minimum recommended yield is 0.5 kg/m², although it may vary, depending on use and surface absorption.

Caution

Do not apply under rainy conditions or when room humidity is above 80%, since the surface may not dry properly. Dilute only with water. Do not use solvents. Let dry before applying a new coating.



MK.I06.R5.REV2

B1852LGX, 1760 Luis M. Drago St., Burzaco, Almirante Brown Industrial District, Buenos Aires (Argentina) / Tel. / Fax: (54-11) 4002-5000
/E-mail: info@megaflex.com.ar / www.megaflex.com.ar / Technical Department: tecnico@megaflex.com.ar

0-800-33-33-649 (MGX)

Images are only illustrative