

ALUMINIZED ASPHALT PAINT



WATERPROOF COATING FOR ALUMINIZED ASPHALT MEMBRANES



Protects asphalt roofs, prolonging their lifespan.

Ultra fast dry solvent-based waterproofer.

Ideal for use with No Crack Aluminum membranes.

Anti-corrosive.

Easily cold-applied.

Reflectant. reduces the temperature of indoor environments.

How Supplied

- 1-L tin can (PAL1)
- 4-L tin can (PAL4)
- 18-L tin can (PAL18)



Features

Waterproof coating for roofings and asphalt covered surfaces. Megaflex Aluminized Asphalt Painting is a bituminous painting made of high-quality special asphalt, solvents, and aluminum pigments.

It is used for painting asphalt roofs. It can also be used as an anti-corrosion protection for metals.

Because of its ultra fast drying capability, it is ideal for works where drying time is crucial. Time to touch dry is 30 minutes. Complete drying takes 1-2 hours, depending on local weather conditions at the time of application.

Where

Waterproofing and protection of asphalt roofs.

Lap joints between NO CRACK aluminum asphalt membranes. Anti-corrosion agent for metal surfaces, such as metal roofs, ducts, pipes, etc.

Application

Application surface should be dry, clean, and free from rust or other release agents.

Before applying, shake the can contents up and down, so that a homogeneous, lump-free mixture is attained.

Agitate often to prevent aluminum pigment sediments to deposit on the bottom of the can. If necessary, dilute with mineral turpentine.

Apply using: Brush, chip brush, paint roller, or paint sprayer. Apply crossover layers, letting dry before each coating. Flammable paint. Apply in cold.

Wash the painting tools using mineral turpentine.

It is strongly recommended not to mix the product with water.

Yield

8 10 m²/L, depending on the surface porosity.

Caution

Flammable, ultra fast dry product, containing highly volatile solvents. Keep away from heat sources or flames. Do not apply indoors. Make sure in all cases to provide an appropriate ventilation



MK.I06.R7.REV2

B1852LGX, 1760 Luis M. Drago St., Burzaco, Almirante Brown Industrial District, Buenos Aires (Argentina) / Tel. /Fax: (54-11) 4002-5000
/E-mail: info@megaflex.com.ar / www.megaflex.com.ar / Technical Department: tecnico@megaflex.com.ar

0-800-33-33-649 (MGX)

Images are only illustrative